



# ***APROTUFF***

**TRUCK & BUS TYRES**

***ENJOY YOUR TRIPS WITH  
APROTUFF TYRES....***



# Brief Introduction

Eastman Impex ..... A Passion for excellence.....

We take pleasure to welcome you to Eastman Impex Family ! ! !

Eastman Impex is a global company, established in 1996 & it has been accredited with ISO 9001:2008. Since 1996 company is growing with increasing trend every year & now adding next step to its growth we develop **APROTUFF** brand .

Our **APROTUFF** brand tires, manufactured on latest equipments and mature technology bears quality certificates like ISO/DOT/ECE/GCC/CCC/INMETRO/SONCAP/E-4 etc.

With high quality, reasonable price and excellent service, we are able to be one of your best tyres suppliers and long term of business partners.

Thanks very much for your attention and time.

## CERTIICATES



ISO 9001  
AS 9100  
BUREAU VERITAS  
Certification



# Manufacture Equipments



# Products Information

## STEER I



Application: Steer Wheel for long distance, also can be used on Trailer Wheel.

Suitable for high speed on good road surface application, with excellent durability, anti-side wear performance.

Longer mileage, Lower noise, Good stone-picking prevention.



- Standard Wheel
- Permitted Wheel
- ⊗ Prohibited Wheel

SIZES LISTS	PR	TREAD DEPTH		LOAD INDEX	SPEED INDEX	STD. RIM
		MM	32NDS	S/D		INCH
11R22.5	16	14.5	18.5	146/143	M	8.25
11R24.5	16	14.5	18.5	149/146	M	8.25
295/75R22.5	14	14.5	18.5	144/141	M	9.00
285/75R24.5	14	14.5	18.5	144/141	M	8.25
295/80R22.5	18	14.5	18.5	152/149	M	9.00
12R22.5	18	14.5	18.5	152/149	M	9.00
315/80R22.5	20	14.5	18.5	156/150	M	9.00

## STEER II



Application: Steer Wheel for long distance, also can be used on Trailer Wheel.

Suitable for high speed on good road surface application, with excellent anti-wet property and sideslip resistance.

Longer mileage, Lower noise, Lower rolling resistance.



- Standard Wheel
- Permitted Wheel
- ⊗ Prohibited Wheel

SIZES LISTS	PR	TREAD DEPTH		LOAD INDEX	SPEED INDEX	STD. RIM
		MM	32NDS	S/D		INCH
11R22.5	16	14.5	18.5	146/143	M	8.25
11R24.5	16	14.5	18.5	149/146	M	8.25
295/80R22.5	18	14.5	18.5	152/149	M	9.00
12R22.5	18	14.5	18.5	152/149	M	9.00
315/80R22.5	20	14.5	18.5	156/150	M	9.00

# Products Information

## DRIVE I



Application: Drive Wheel for medium mileage load series. Close Shoulder designs, the block pattern offer excellent drive force and good braking performance on paved road condition. Excellent load capability, Longer mileage, Super Durability.



- Standard Wheel
- Permitted Wheel
- ⊗ Prohibited Wheel

SIZES LISTS	PR	TREAD DEPTH		LOAD INDEX	SPEED INDEX	STD. RIM
		MM	32NDS	S/D		INCH
11R22.5	16	19.5	24.5	146/143	L	8.25
11R24.5	16	19.5	24.5	149/146	L	8.25
295/75R22.5	14	19.5	24.5	144/141	L	9.00
285/75R24.5	14	19.5	24.5	144/141	L	8.25

## DRIVE II



Application: Drive Wheel for medium mileage load series. Open Shoulder designs, the block pattern offer excellent drive force and anti-peeling performance on paved and unpaved road. Excellent load capability, Longer mileage, Super Durability.



- Standard Wheel
- Permitted Wheel
- ⊗ Prohibited Wheel

SIZES LISTS	PR	TREAD DEPTH		LOAD INDEX	SPEED INDEX	STD. RIM
		MM	32NDS	S/D		INCH
11R22.5	16	19.5	24.5	146/143	L	8.25
11R24.5	16	19.5	24.5	149/146	L	8.25
295/80R22.5	18	19.5	24.5	152/149	L	9.00
12R22.5	18	19.5	24.5	152/149	L	9.00
315/80R22.5	20	19.5	24.5	156/150	L	9.00

# Products Information

## MIX I



Application: All Position Wheels for On/Off use.  
Mixed pattern, Suitable for mixed road surface and relatively poor road condition with sideslip resistance.  
Excellent crack & tear resistance, High speed, Long mileage.



- Standard Wheel
- Permitted Wheel
- ⊗ Prohibited Wheel

SIZES LISTS	PR	TREAD DEPTH		LOAD INDEX	SPEED INDEX	STD. RIM
		MM	32NDS	S/D		INCH
11R22.5	16	14.5	18.5	146/143	M	8.25
11R24.5	16	14.5	18.5	149/146	M	8.25
12R22.5	18	14.5	18.5	152/149	M	9.00
315/80R22.5	20	14.5	18.5	156/150	M	9.00
13R22.5	18	14.5	18.5	154/151	L	9.75
9.00R20	16	15.5	19.5	144/142	K	7.00
10.00R20	18	16.5	21.0	149/146	K	7.50
11.00R20	18	17.0	21.5	152/149	K	8.00
12.00R20	18	17.5	22.0	154/151	K	8.50
12.00R24	20	16.0	20.0	160/157	K	8.50

## MIX II



Application: All Position Wheels for On/Off use.  
Mixed pattern, Suitable for mixed road surface and relatively poor road condition with high loading capability.  
Excellent crack & tear resistance, Good anti-uneven wear character.



- Standard Wheel
- Permitted Wheel
- ⊗ Prohibited Wheel

SIZES LISTS	PR	TREAD DEPTH		LOAD INDEX	SPEED INDEX	STD. RIM
		MM	32NDS	S/D		INCH
9.00R20	16	15.5	19.5	144/142	K	7.00
10.00R20	18	16.5	21.0	149/146	K	7.50
11.00R20	18	17.0	21.5	152/149	K	8.00
12.00R20	18	17.5	22.0	154/151	K	8.50
12.00R24	20	16.0	20.0	160/157	K	8.50

# Products Information

## DRIVE III



Application: Drive Wheel for medium mileage load series.  
Suitable for highway and good road condition, with powerful driving force, anti-peeling & anti-wear performance.  
Excellent load capability, Longer mileage, High Speed.



- Standard Wheel
- Permitted Wheel
- ✗ Prohibited Wheel

SIZES LISTS	PR	TREAD DEPTH		LOAD INDEX	SPEED INDEX	STD. RIM
		MM	32NDS	S/D		INCH
295/80R22.5	18	18.5	23.5	152/149	K	9.00
12R22.5	18	18.5	23.5	152/149	K	9.00
315/80R22.5	20	18.5	23.5	156/150	K	9.00

## DRIVE IV



Application: Drive Wheel for On/Off Road use.  
Suitable for mix road use and relatively poor road condition with excellent traction character.  
Excellent load capability, Longer mileage, Good anti-wearing.



- Standard Wheel
- Permitted Wheel
- ✗ Prohibited Wheel

SIZES LISTS	PR	TREAD DEPTH		LOAD INDEX	SPEED INDEX	STD. RIM
		MM	32NDS	S/D		INCH
295/80R22.5	18	18.5	23.5	152/149	K	9.00
12R22.5	18	18.5	23.5	152/149	K	9.00
315/80R22.5	20	18.5	23.5	156/150	K	9.00
13R22.5	18	18.5	23.5	154/151	K	9.75

# Products Information

## MIX III



Application: All Position Wheels for long mileage load series.  
New designed pattern, Suitable for well paved road condition with excellent durability.  
Standard load, Low heat build-up, High speed.



- Standard Wheel
- Permitted Wheel
- ⊗ Prohibited Wheel

SIZES LISTS	PR	TREAD DEPTH		LOAD INDEX	SPEED INDEX	STD. RIM
		MM	32NDS	S/D		INCH
12.00R24	20	16.0	20.0	160/157	K	8.50

## MIX IV



Application: All Position Wheels for long mileage load series.  
New designed pattern, Suitable for well paved road condition with excellent durability.  
Standard load, Low heat build-up, High speed.



- Standard Wheel
- Permitted Wheel
- ⊗ Prohibited Wheel

SIZES LISTS	PR	TREAD DEPTH		LOAD INDEX	SPEED INDEX	STD. RIM
		MM	32NDS	S/D		INCH
9.00R20	16	15.5	19.5	144/142	K	7.00
10.00R20	18	16.5	21.0	149/146	K	7.50
11.00R20	18	17.0	21.5	152/149	K	8.00
12.00R20	18	17.5	22.0	154/151	K	8.50

# Products Information

## TRAILER I



Application: Trailer Wheel for regional use.  
 Suitable for high and medium speed on good road surface with excellent anti-skid-side character and drainage performance.  
 Excellent loading capacity, Low rolling resistance, Low noise.



- Standard Wheel
- Permitted Wheel
- ✘ Prohibited Wheel

SIZES LISTS	PR	TREAD DEPTH		LOAD INDEX	SPEED INDEX	STD. RIM
		MM	32NDS	S/D		INCH
385/65R22.5	20	15.5	19.5	160	L	11.75

## TRAILER II



Application: Trailer Wheel for regional use, also can be used for Steer Wheel.  
 Suitable for high speed on paved road surface with excellent anti-skid-side character and durability performance.  
 Excellent loading capacity, Low rolling resistance, Low noise.



- Standard Wheel
- Permitted Wheel
- ✘ Prohibited Wheel

SIZES LISTS	PR	TREAD DEPTH		LOAD INDEX	SPEED INDEX	STD. RIM
		MM	32NDS	S/D		INCH
385/65R22.5	20	15.5	19.5	160	L	11.75

# Products Information

## BLOCK I



Application: Drive Wheel for short distance, also can be used on Steer Wheel.

Suitable for low speed ride on bad road condition, specially for mining area, with powerful grip and high loading ability.

Longer Mileage, Strong Structure, Good anti-wear performance.



- Standard Wheel
- Permitted Wheel
- ⊗ Prohibited Wheel

SIZES LISTS	PR	TREAD DEPTH		LOAD INDEX	SPEED INDEX	STD. RIM
		MM	32NDS	S/D		INCH
9.00R20	16	16.5	21.0	144/142	J	7.00
10.00R20	18	17.5	22.0	149/146	J	7.50
11.00R20	18	18.5	23.5	152/149	J	8.00
12.00R20	18	19.5	24.5	154/151	J	8.50

## BLOCK II



Application: Drive Wheel for short distance, also can be used on Steer Wheel.

Suitable for low or middle speed ride on/off road condition, with powerful grip and high loading ability.

Longer Mileage, Strong Structure, Good anti-wear performance.



- Standard Wheel
- Permitted Wheel
- ⊗ Prohibited Wheel

SIZES LISTS	PR	TREAD DEPTH		LOAD INDEX	SPEED INDEX	STD. RIM
		MM	32NDS	S/D		INCH
12.00R24	20	16.0	20.0	160/157	K	8.50



*Your Reliable Tyre Supplier .....*

## **Eastman IMPEX**

INDUSTRIAL AREA – C, SUA ROAD DHANDHARI KALAN, LUDHIANA 141010  
TEL : +91-161-3044095, 2511603-05 FAX : +91-161-5066360  
EMAIL : info@eastmanimpex.com sdogra@eastmanimpex.com

WEBSITE

[www.eastmanimpex.com](http://www.eastmanimpex.com)

China Office:

#1105, 369. Winner Tower Zhongshan Nanlu, Nanjing-210001 (JIANGSU, CHINA)  
Phone No: +86-25-58074546